

17-260 Hz +/- 3 dB (standard mode)
19-260 Hz +/- 3 dB (sealed mode)
Expect 2-3 Hz deeper extension in small to mid-size rooms.

2-meter ground plane away from reflective structures (quasi-anechoic).
Roll-off slope specifically optimized to take maximum advantage of available room gain.

Subwoofer Specs:

Protective non-resonant extra-thick ABS fabric mesh grille
Iso-elastomer feet included
Extra heavy-duty, high current power cord 6'
Quick Start Guide
Port Plugs (free upon request)
Unbalanced stereo input/output
Speaker Level Stereo Input
Auto/On and Trigger options through app, 3-12V AC/DC trigger
RoHS compliant, lead-free construction, world-wide safety certifications
Green 0.5-watt low standby power consumption

Dual 2.5-inch ports
Dimensions (w/ grille): 18.9" (479mm) H X 15" (380mm) W X 20" (509mm) D
Dimensions (without grille): 18.9" (479mm) H X 15" (380mm) W X 19.2" (488mm) D
Shipped Dimensions: 23.4" (594mm) H 19.9" (506mm) W X 24.4" (619mm) D
Weight (unboxed): 42.5lbs (19.3kg) with Grille
Shipped Weight: 51.6lbs (23.4kg)

Driver Specs:

All-new proprietary 12-inch long-throw driver with high-

Dual 24-strand copper-alloy high-temperature leads
Proprietary injection molded

precision tuned overhung
motor configuration.

9.26lb (4.2kg) pound Woofer
with 6.91lb (3.14kg) pounds
motor

13.1mm Xmax, 26.8mm
Xmech precision aligned
excursion

1.5" diameter Voice Coil with
high current 6-layer high-
purity copper wire windings
Premium high-purity copper
voice coil winding design
minimizes distortion and
power compression with
maximum heat dissipation,
linearity, and tuned magnetics
for high excursion

Two-piece high grade
oversized Y35 Ferrite magnet
motor

High Temperature 3003-H18
aluminum former/bobbing
6" composite cotton-poly
extreme excursion linear
spider

gasket and NBR extreme-
excursion surround

Lightweight treated Fiber
Composite cone for enhanced
sensitivity and transient
response

Top plate assembly with low
carbon 1010 steel for optimal
magnetics

Oversized low carbon 1008
steel T-yoke with integrated
pole piece extension for
maximum cooling and
electromagnetics

12" premium powder coated
basket with FEA optimized
analysis for maximum rigidity,
tensile strength, and energy
transference

Oversized motor system for
driving full excursion and
industry best SPL, with
pinpoint transient speed
Precision machining for motor
and narrow tolerance
suspension parts ensure
flawless linearity at full range
of excursion

SVS Sledge-325D Amplifier Specs:

325 watts RMS, 820+ watts
peak power output Class D
design
50Mhz Analog Devices Audio
DSP, high resolution double

Customer EQ and DSP limiter
settings specifically for the
1000 Pro
Input impedance 16kohm
(unbalance RCA)

precision 56bit filtering
Wide input voltage bandwidth
compliant for consumer and
pro audio up to 4V line level
input.

High efficiency LLC resonant
SMPS with 17A 650V
MOSFET, resonant switching
results in lower EMI and
highest efficiency.

Cool-running Class D
amplifier switching topology
with massive 34A 120V

MOSFET's

SVS BLE control app for iOS
and Android contains 3
complete name-able and
customizable User presets,
supports IOS (iphone5 or
newer or Android (4.42 or
newer), 3 PEQ's per preset,
adjustable low pass, phase,
polarity, room gain
compensation, and control for
best alignment with speakers.

Input impedance 20kohm
(speaker level)

New Intelligent Feature
control (IFC) user interface on
the amplifier with bright blue
11 LED bar display and easy
push-button controls.

SVS App Specs:

Bluetooth controlled
subwoofer DSP smartphone
app works with iOS, Android
and Amazon operating
systems.

Easiest and most convenient
way to adjust crossover
frequencies, parametric EQ,
polarity, room gain and all

Unique bidirectional feedback
shows adjustments in real
time on both app and
subwoofer interface.

Easy-to-follow tutorial
provides clear guidance for all
functions.

other bass management functions.

Three convenient custom presets allow for perfect tuning in any room or system, from your favorite seat.

Accessories:

Protective non-resonant extra-thick ABS fabric mesh grille
Iso-elastomer feet included

Extra heavy-duty, high current 6-foot power cord
Quick Start Guide